



SELF- TAPPING SCREWS

SECURITY SCREWS **Button Head
Six Lobe Recess**



SIX-LOBE PIN-IN BUTTON HEAD SECURITY SCREWS							
Screw Size	D		H		P	R	Driver Size
	Head Dimensions				Recess Dimensions		
	Head Diameter		Head Height		Pin Diameter	Recess Depth	
	Max	Min	Max	Min	Ref	Min	
6	0.262	0.250	0.073	0.063	0.030	0.035	T-10
8	0.312	0.298	0.087	0.077	0.040	0.047	T-15
10	0.361	0.347	0.101	0.091	0.070	0.057	T-25
12	0.412	0.397	0.114	0.104	0.068	0.068	T-25
1/4	0.437	0.419	0.132	0.122	0.080	0.067	T-27
Tolerance on Length	Up to 1" length, incl..				Over 1"		
	± 0.03				± 0.05		

Description	A thread forming tapping screw with wider spaced threads than a Type-AB, a rounded head profile and a gimlet point. The six-lobed recess has a cylindrical pin attached to the center of the base of the recess that extends to the top profile of the head
Applications/ Advantages	For self-starting in thin metal or resin-filled plywood where the risk of unwanted tampering is high. The pin-in recess provides a deterrent against loosening the screw, since a standard six-lobe screwdriver cannot engage with the recess. A specially designed driver--not commonly available in the retail market--is required to install or loosen the screw. The stainless screw offers resistance to atmospheric corrosion.
Material	18-8 Stainless

This page prints with a watermark